

Model <sup>1</sup>	6 PLUS	8 PLUS	8 TWIN	12 TWIN
<b>Technology</b>	BAF	BAF	BAF	BAF
<b>Tank Material</b>	Reinforced Concrete	Reinforced Concrete	Reinforced Concrete	Reinforced Concrete
<b>Population Equivalent (PE)</b>	6	8	8	12
<b>Daily Hydraulic Loading (Litres)</b>	900	1,200	1,200	1,800
<b>Design Dwelling Size (Bedrooms)</b>	1 to 4	2 to 6	2 to 6	4 to 10
<b>Outlet Types Available</b>	Gravity or Pumped	Gravity or Pumped	Gravity or Pumped	Gravity or Pumped
<b># of Chambers</b>	5	5	4	4
<b># of Tanks</b>	Single Tank	Single Tank	2	2
<b>Tank Weight ~</b>	6.75 tonne	6.75 tonne	4.5 tonne (each)	4.5 tonne (each)
<b>Total Capacity</b>	7m <sup>3</sup> / 1,850 gal	7m <sup>3</sup> / 1,850 gal	8m <sup>2</sup> / 2,100 gal	8m <sup>2</sup> / 2,100 gal
<b>Service Interval</b>	1 year	1 year	1 year	1 year
<b>Warranty Period ^</b>	5 years	5 years	2 years	2 years
<b>Excavation Size (m) *</b>	3.5L x 2.3W x 1.45BI	3.5L x 2.3W x 1.45BI	3.5L x 3.6W x 1.45BI	3.5L x 3.6W x 1.45BI
<b>Inlet Pipe Invert from Base (m)</b>	1.45	1.45	1.45	1.45
<b>Sludge Return</b>	Variable Airlift	Variable Airlift	Variable Airlift	Variable Airlift
<b>Desludge Interval @ 30% occupancy</b>	7 years	6 years	7 years	5 years
<b>Desludge Interval @ 60% occupancy</b>	5 ½ years	4 years	5 years	3 years
<b>Desludge Interval @ 90% occupancy</b>	4 years	3 years	4 years	2 years

\* L = Length, W = Width, BI = Below Inlet ^ subject to terms and conditions. <sup>1</sup> other model's also available by request.

~ = excluding risers. Data correct as of 30/11/2021, the data contained above is subject to change without prior notice.